



TONGYU Lithium Polymer Battery Series

Model Number	Capacity (Ah)	Voltage (V)	Dimension(mm)			Weight(Kg)
	mAh		Thickness (± 0.3)	Width (±0.5)	Height (±1)	Approx
T-Y401320	55	3.7	4	13	20	1.5
T-Y351230	80	3.7	3.5	12	30	2.0
T-Y301730	100	3.7	3	17	30	2.5
T-Y-352036	150	3.7	3.5	20	36	4.0
T-Y522030	210	3.7	5.2	20	30	5.5
T-Y452036	250	3.7	4.5	20	36	5.5
T-Y552036	340	3.7	5.5	20	36	7.0
T-Y-402060	400	3.7	4	20	60	9.0
T-Y483048	650	3.7	4.8	30	48	13.0
T-Y383458	750	3.7	3.8	34	58	14.5
T-Y453450	800	3.7	4.5	34	50	15.0
T-Y383560	850	3.7	3.8	35	60	15.0
T-Y723048	1000	3.7	7.2	30	48	20.0
T-Y503759	1250	3.7	5	37	59	26.0
T-Y603480	1500	3.7	6	34	80	30.0
T-Y507062	2100	3.7	5	70	62	45.0
T-Y3048166	2400	3.7	3	48	166	50.0
T-Y28103122	2700	3.7	2.8	103	122	63.0
T-Y6045135	3400	3.7	6	45	135	72.0
T-Y-7535135	3200	3.7	7.5	35	135	72.0
T-Y5860150	4400	3.7	5.8	60	150	98.0
T-Y6548166	5300	3.7	6.5	48	166	106.0
T-Y-1587062	6200	3.7	15.8	70	62	130.0
T-Y-9240160	4600	3.7	9.2	40	160	113.0
T-Y6848166	5000	3.7	6.8	48	166	118.0

T-Y6549220	6800	3.7	6.5	49	220	140.0
T-Y9652220	9500	3.7	9.6	52	220	218.0
T-Y8067220	10000	3.7	8	67	220	240.0
T-Y8867220	10500	3.7	8.8	67	220	260.0
T-Y9667220	10000	3.7	9.6	67	220	270.0
T-Y7098140	8300	3.7	7	98	140	200.0
T-Y82125200	17000	3.7	8.2	125	200	380.0

Note:

1) Charge: 0-45°C, Discharge: -10--+45°C, Stock: -10--+35°C

2) Any other models not find in the index, please contact TONGYU

3) We can design and assemble pack for 3S 5S 7S 8S 10S 13S...

www.tongyu-tech.com