



TONGYU Lithium-ion Cylindrical Battery Index



Cylindrical Li-ion batteries

Model	Nominal Voltage (V)	Capacity		Dimension		Weight Approx (g)
		Typical (mAh)	Nominal (mAh)	Diameter (mm)	Height (mm)	
ICR08200	3.7	80	75	8.4	22	2.9
ICR08600	3.7	300	280	8.4	60.5	9
ICR10120	3.7	50	45	10.2	11.2	2.4
ICR10220	3.7	120	110	10.2	22.3	5
ICR10430	3.7	320	300	10.2	42.5	9
ICR10440	3.7	320	300	10.2	43.5	9
ICR14430	3.7	650	620	14.1	43	16
ICR14500	3.7	750	720	14.1	50	18
ICR14650	3.7	1100	1050	14.1	65	24
ICR17280	3.7	600	550	16.5	28	15
ICR17335	3.7	700	650	16.8	34.5	18
ICR17500	3.7	1100	1050	16.8	50	27
ICR17650	3.7	1600	1500	16.8	65	36
ICR18490	3.7	1400	1350	18.3	49	33
ICR18650	3.7	1800	1750	18.3	64.5	43
ICR18650	3.7	1900	1850	18.3	64.5	43
ICR18650	3.7	2000	1950	18.3	64.5	43
ICR18650	3.7	2100	2050	18.3	64.5	44
ICR18650	3.7	2200	2150	18.3	64.5	45

Cylindrical Li-ion High Drain Batteries

Model	Nominal Voltage (V)	Capacity		Dimension(max)		Weight Approx (g)
		Typical (mAh)	Nominal (mAh)	Diameter (mm)	Height (mm)	
ICR14500MP	3.7	600	550	14.5	49	18
ICR17280MP	3.7	500	450	16.8	28.5	16
ICR18500MP	3.7	1050	1000	18.3	50	28
ICR18650MP	3.7	1050	1000	18.3	64.5	31
ICR18650MP	3.7	1350	1300	18.3	64.5	32
ICR18650MP	3.7	1500	1450	18.3	64.5	33
ICR26650MP	3.7	3300	3200	26.3	64.5	

Note: Any other models not find in the index, please contact TONGYU